

ODM Wire Electrical Copper Connector Terminal Lug

Basic Information

Place of Origin: chinaBrand Name: jinshunlai

Certification: ISO, AISI, ASTM, GB, EN, DIN

Model Number: 0.1mm-900mm

Minimum Order Quantity: 1kg

Price: Contact Us

Packaging Details: Waterproof Paper, Steel Strip Packed and

other Standard Export Seaworthy Package,

or customized package

• Delivery Time: 5day

Payment Terms: L/C, T/T, Western Union

• Supply Ability: 90000ton



Product Specification

• Chemical Composition: Cu-Ni Excellent · Corrosion Resistance: 8.9 G/cm3 . Density: • Electrical Conductivity: ≤20%IACS . Elongation: 30-40% Formability: Good · Hardness: High . Heat Treatment: Annealing Machinability: Good

Melting Point: 1453-1475°C
Name: Copper Connector
Tensile Strength: 400-550 MPa
Thermal Conductivity: 50-70 W/mK
Weldability: Good

Weldability: GoodYield Strength: 200-350 MPa



More Images



Product Description
ODM Wire Electrical Copper Connector Terminal Lug
Application
Terminal connectors are used to connect tap conductor to power equipments (transformer,circuit breaker,disconnect switch.etc)or to wall bushing of substation. Aluminum connectors are Also used to connect the tap conductor of T-connector. The connectors inclede conpressive-type and bolted, both types have angle of 0°, 30° and 90° with the direction of tap conductor.

Specification

Product name	DTL Bimetal Cable Lugs
Color	AS Picture
Delivery time	Quantity
Usage	Accessories
OEM/ODM	Customization Service Provided





+86-17763564398





© copper-solid.com

32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China