

C83600 Eccentric Cast Bronze Bushing Cone Crusher Oil Impregnated

Basic Information

Place of Origin: chinaBrand Name: jinshunlai

• Certification: ISO, AISI, ASTM, GB, EN, DIN

Model Number: 0.1mm-900mm

Minimum Order Quantity: 1kg

• Price: Contact Us

Packaging Details: Waterproof Paper, Steel Strip Packed and

other Standard Export Seaworthy Package,

or customized package

• Delivery Time: 5day

Payment Terms: L/C, T/T, Western Union

• Supply Ability: 90000ton



Product Specification

• Chemical Composition: Cu-Ni Excellent · Corrosion Resistance: 8.9 G/cm3 . Density: • Electrical Conductivity: ≤20%IACS . Elongation: 30-40% Formability: Good . Hardness: High . Heat Treatment: Annealing Machinability: Good

Melting Point: 1453-1475°C
Name: Copper Nickel Alloy
Tensile Strength: 400-550 MPa
Thermal Conductivity: 50-70 W/mK
Weldability: Good

Yield Strength: 200-350 MPa



More Images



Product Description

Key attributes

Industry-specific attributes

Applicable Industries	Building Material Shops, Manufacturing Plant, Machinery Repair Shops, Retail, Construction works
Туре	sleeve
Material	Copper Alloy

Other attributes

Place of Origin	Shandong, China
Brand Name	jinshunlai
Model Number	M5M6M8M12M13M15M16M20M25
Product name	Copper bushings
Size	M5M6M8M12M13M15M16M20M25M30
Usage	measure sleeves
density	8.7 (g/cm)
Max Dynamic Load	60 N/mm2
Max Linear Velocity(Grease) m/s	0.85

Packaging & delivery

Selling Units:	Single item ——
Single package size:	6X6X5 cm
Single gross weight:	0.300 kg
Packane Tyne:	Packing Details · Small piece goods are self-sealing had packing ± carton

Copper Wuxi Jinnuo copper Co.,Ltd







sales01@shuangheyisteel.com



© copper-solid.com

